



W1940

OPTIC

- LED: 19× 40W RGBW LED
- Beam angle: 4 ~ 30° - Field angle: 5~50°
- Color temperature: 2000K~100000K
- Lumens: 11500 Lm
- CRI: 80
- LED Lifetime: 50000 H

EFFECT

- Uniform RGBW color mixing system and rainbow effect, single point LED control - Create unlimited dynamic, unlimited color changes
- Strobe: 1 ~ 25Hz

SOFTWARE

- Quick and easy to update software via DMX signal or USB
- Silent fan, intelligent speed regulation
- Intelligent temperature protection to ensure the service life of LED

CONTROL & PROGRAM

- Channel: 12/19/45CH
- Protocol: DMX512, RDM
- Data connector: 3PIN XLR
- Display: 1.8 LCD display, with rechargeable battery, you can enter the menu to set address code and other Settings without power on

OTHER

- IP rating: IP30
- Work environment: -40°C ~ 45°C
- Startup environment: -20°C ~ 45°C

HOUSING

- Aluminum alloy structure + plastic (VO)
- Fan cooling

POWER CONSUMPTION

- Voltage: AC 110V-240V 50/60Hz
- Rated power: 900 W

SIZE & WEIGHT

- Size: 380mm×234mm×470mm
- N.W: 19kg

