



W740



OPTIC

- LED: 7 × 40W RGBW LED
- Beam angle: 3.8 ~54°
- Color temperature: 2000K~100000K
- Lumens: 4400 Lm
- CRI: 95
- LED Lifetime: 50000 H

EFFECT

- Uniform RGBW color mixing system and rainbow effect, single point LED control
- Create unlimited dynamic, unlimited color changes
- Strobe: 1 ~ 25Hz

SOFTWARE

- Quick and easy to update software via DMX signal or USB
- Silent fan, intelligent speed regulation
- Intelligent temperature protection to ensure the service life of LED

CONTROL & PROGRAM

- Channel: 12/19/45CH
- Protocol: DMX512, RDM
- Data connector: 3PIN XLR
- Display: 1.8 LCD display, with rechargeable battery, you can enter the menu to set address code and other Settings without power on

OTHER

- IP rating: IP30
- Work environment: -40°C ~ 45°C
- Startup environment: -20°C ~ 45°C

PAN & TILT MOVEMENT

- Pan: 540° or 630° 8bit/16bit
- Tilt: 270° 8bit/16bit

HOUSING

- Aluminum alloy structure + plastic (VO)
- Fan cooling

POWER CONSUMPTION

- Voltage: AC 110V-240V 50/60Hz
- Rated power: 320 W

SIZE & WEIGHT

- Size: 250 × 184 × 329 mm
- N.W: 6.5 kgs

